

Installation advice

Panels have a unique code at the bottom left corner of each panel. Codes run from A1 at the bottom left of the wall, ascending to A2, A3 etc. On top of that then comes row 2, with the first panel being B1, B2, B3 Etc. Row 3 then starts with C1, and so on.

C1	C2	C3	C4	C5	C6
B1	B2	B3	B4	B5	B6
A1	A2	A3	A4	A5	A6

Positioning panels

It is important that the panels are mounted at the correct distance from each other. Make sure that the distance between the pebbles, on the 2 adjacent panels have the same joint width as bricks sitting in the middle of a panel. This prevents the panel contours from being visible in the entire image.

If required, we offer:
the Mozawall application tool.

Wall pre-treatment

The wall should be moisture-free and moisture-resistant. If necessary, a moisture-resistant coating can be applied in advance. Prime the substrate with PCI GISOGRUND*** (*consumption approx. 0.21 Ltr. p/m²*).

Gluing Mozawall

Fully seal the back of the Mozawall panels with PCI NANOLIGHT WHITE*** i.e. with the flat side of the glue trowel according to the Buttering Floating method.

Make sure that all cavities are filled with adhesive.

Using a 4 mm notched trowel, apply adhesive beads to the wall using PCI NANOLIGHT WHITE***. Push the Mozawall into place with a sliding movement. (*consumption approx. 2 kg per m²*)

Grouting Mozawall

The front of the Mozawall is grouted and inlaid with PCI NANOFUG PREMIUM*** available in 28 colors. (*consumption 0,84 Kg. p/m²*)

Advice: Clean off excess grout quickly and not too dry. If cleaning is done too dry, the abrasive effect can cause the top layer of the panels to become slightly dull. By washing quickly and not too dry, you can prevent this and preserve the gloss of the panel.

High quality professional gluing & grouting.

For special applications: Chemical resistant, outdoor use, vandalism resistant, high quality even grouting, moisture impermeable, sauna, swimming pool use to bond PCI DURAPROX PREMIUM***. For grouting you can also use PCI DURAPROX PREMIUM in 17 colors (*consumption 4 kg/m²*).

*** or a similar product from another brand

